საქართველოს სტანდარტი

დაცვა ელვისგან - ნაწილი 3: ფიზიკურად დაზიანებული სტრუქტურები და სასიცოცხლო საფრთხე

> საქართველოს სტანდარტებისა და მეტროლოგიის ეროვნული სააგენტო თბილისი

საინფორმაციო მონაცემები

1 შემუშავებულია საქართველოს სტანდარტების და მეტროლოგიის ეროვნული სააგენტოს სტანდარტების დეპარტამენტის მიერ

2 დამტკიცებულია და შემოღებულია სამოქმედოდ საქართველოს სტანდარტების და მეტროლოგიის ეროვნული სააგენტოს 2019 წლის 30 სექტემბრის № 68 განკარგულებით

3 მიღებულია გარეკანის თარგმნის მეთოდით საერთაშორისო ელექტროტექნიკური კომისიის სტანდარტი იეკ 62305-3:2010 "დაცვა ელვისგან - ნაწილი 3: ფიზიკურად დაზიანებული სტრუქტურები და სასიცოცხლო საფრთხე"

4 პირველად

5 რეგისტრირებულია საქართველოს სტანდარტების და მეტროლოგიის ეროვნული სააგენტოს რეესტრში: 2019 წლის 30 სექტემბერი №268-1.3-015246

დაუშვებელია წინამდებარე სტანდარტის სრული ან ნაწილობრივი კვლავწარმოება, ტირაჟირება და გავრცელება სსიპ საქართველოს სტანდარტებისა და მეტროლოგიის ეროვნული სააგენტოს ნებართვის გარეშე





Edition 2.0 2010-12

INTERNATIONAL STANDARD



Protection against lightning – Part 3: Physical damage to structures and life hazard



IEC 62305-3:2010(E)



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2010 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland Email: inmail@iec.ch Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

Catalogue of IEC publications: <u>www.iec.ch/searchpub</u>

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

IEC Just Published: <u>www.iec.ch/online_news/justpub</u>

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

Electropedia: <u>www.electropedia.org</u>

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

Customer Service Centre: <u>www.iec.ch/webstore/custserv</u>

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: <u>csc@iec.ch</u> Tel.: +41 22 919 02 11 Fax: +41 22 919 03 00





Edition 2.0 2010-12

INTERNATIONAL STANDARD



Protection against lightning – Part 3: Physical damage to structures and life hazard

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 29.020; 91.120.40

ISBN 978-2-88912-282-0

CONTENTS

FO	REWO	DRD		7
INT	RODI	JCTION	۱	10
1	Scop	e		11
2	Norm	native re	eferences	11
3	Term	s and d	efinitions	12
4	Liaht	nina pro	otection system (LPS)	15
-	4 1	Class	of LPS	15
	4.2	Design	of the LPS	16
	4.3	Contin	uity of steelwork in reinforced concrete structures	16
5	Exter	nal ligh	tning protection system	17
	5.1	Gener	al	17
		5.1.1	Application of an external LPS	17
		5.1.2	Choice of external LPS	17
		5.1.3	Use of natural components	17
	5.2	Air-ter	mination systems	18
		5.2.1	General	18
		5.2.2	Positioning	18
		5.2.3	Air-terminations against flashes to the side of tall structures	19
		5.2.4	Construction	20
		5.2.5	Natural components	20
	5.3	Down-	conductor systems	21
		5.3.1		21
		5.3.2	Positioning for an isolated LPS	22
		5.3.3	Positioning for a non-isolated LPS	22
		5.3.4	Construction	23
		5.3.5		23 24
	51	5.5.0 Earth t	termination system	24
	5.4	∟ann- 5 4 1	General	24
		542	Earthing arrangement in general conditions	24
		543	Installation of earth electrodes	26
		5.4.4	Natural earth electrodes	27
	5.5	Compo	onents	27
		5.5.1	General	27
		5.5.2	Fixing	28
		5.5.3	Connections	28
	5.6	Materi	als and dimensions	29
		5.6.1	Materials	29
		5.6.2	Dimensions	29
6	Interi	nal light	ning protection system	31
	6.1	Gener	al	31
	6.2	Lightni	ing equipotential bonding	32
		6.2.1	General	32
		6.2.2	Lightning equipotential bonding for metal installations	32
		6.2.3	Lightning equipotential bonding for external conductive parts	33
		6.2.4	Lightning equipotential bonding for internal systems	34

		6.2.5	Lightning equipotential bonding for lines connected to the structure to	
			be protected	. 34
	6.3	Electric	cal insulation of the external LPS	. 35
		6.3.1 6.2.2	General	. 35
		0.3.Z	Detailed approach	. 30 36
7	Maint	enance	and inspection of an LPS	. 37
•	7 1	Genera	al	37
	7.2	Applica	ation of inspections	. 37
	7.3	Order	of inspections	. 37
	7.4	Mainte	nance	. 37
8	Prote	ction m	easures against injury to living beings due to touch and step voltages	. 37
	8.1	Protect	ion measures against touch voltages	. 37
	8.2	Protect	ion measures against step voltages	. 38
Anr	nex A	(normat	ive) Positioning the air-termination system	. 39
Anr	nex B	(normat	ive) Minimum cross-section of the entering cable screen in order to	15
avu Apr		igeious (informa	sparking	.45
Ann		(11101118	anve) Evaluation of the separation distance s	. 40
risk	of ex	(normat plosion	ive) Additional information for LPS in the case of structures with a	. 52
Anr	nex E	(informa	ative) Guidelines for the design, construction, maintenance and	
insp	pectio	n of ligh	tning protection systems	. 59
Bib	liogra	ohy		156
Lia	uro 1	Drotor	stion angle corresponding to the close of LDS	10
Figi	ure i ·	- Protec	ction angle corresponding to the class of LPS	. 19
Fig	ure 2 ·		n a down-conductor	. 23
Figi	ure 3 -		um length I ₁ of each earth electrode according to the class of LPS	. 25
Fig	ure A.	1 – Volu	ime protected by a vertical air-termination rod	. 39
Fig	ure A.	2 – Volu	me protected by a vertical air-termination rod	. 40
Fig	ure A.	3 – Volu	me protected by a wire air-termination system	. 40
Fig	ure A. tectior	4 – Volu nanale	Ime protected by isolated wires combined in a mesh according to the method and rolling sphere method	. 41
Fig	ure A.	5 – Volu	Ime protected by non-isolated wires combined in a mesh according to	
the	mesh	method	I and the protection angle method	. 42
Fig met	ure A.	6 – Des	ign of an air-termination system according to the rolling sphere	. 43
Fig	ure C.	1 – Valu	ues of coefficient <i>k</i> _c in the case of a wire air-termination system	. 46
Fig	ure C.	2 – Valu	ues of coefficient k_c in the case of multiple down-conductors system	. 47
Fig the	ure C. ridae	3 – Valı	ues of coefficient k_{c} in the case of a sloped roof with air-termination on	. 49
Fig	ure C.	4 – Exa	mples of calculation of the separation distance in the case of multiple	-
dow	vn-cor	ductors	with an interconnecting ring of the down-conductors at each level	. 50
Fig with	ure C. n a mu	5 – Valu Iltiple do	ues of coefficient <i>k</i> _c in the case of a meshed air-termination system, pwn-conductors system	. 51
Fig	ure E.	1 – LPS	design flow diagram	. 61
Fig	ure E.	2 – LPS	design for a cantilevered part of a structure	. 67
Fia	ure E	3 – Mea	suring the overall electrical resistance	. 68
9				

Figure E.4 – Equipotential bonding in a structure with a steel reinforcement	70
Figure E.5 – Typical methods of joining reinforcing rods in concrete (where permitted)	71
Figure E.6 – Example of clamps used as joints between reinforcing rods and conductors	72
Figure E.7 – Examples for connection points to the reinforcement in a reinforced concrete wall.	73
Figure E.8 – Use of metallic facade as natural down-conductor system and connection of facade supports	77
Figure E.9 – Connection of the continuous strip windows to a metal facade covering	78
Figure E.10 – Internal down-conductors in industrial structures	81
Figure E.11 – Installation of bonding conductors in reinforced concrete structures and flexible bonds between two reinforced concrete parts	83
Figure E.12 – Protection angle method air-termination design for different heights according to Table 2	87
Figure E.13 – Isolated external LPS using two isolated air-termination masts designed according to the protection angle air-termination design method	88
Figure E.14 – Isolated external LPS using two isolated air-termination masts, interconnected by horizontal catenary wire	89
Figure E.15 – Example of design of an air-termination of a non-isolated LPS by air- termination rods	90
Figure E.16 – Example of design of an air-termination of a non isolated LPS by a horizontal wire according to the protection angle air-termination design method	91
Figure E.17 – Protected volume of an air- termination rod on a sloped surface using the protection angle design method	92
Figure E.18 – Design of an LPS air-termination conductor network on a structure with complicated shape	93
Figure E.19 – Design of an LPS air-termination according to the protection angle method, mesh method and general arrangement of air-termination elements	94
Figure E.20 – Space protected by two parallel air-termination horizontal wires or two air-termination rods ($r > h_t$)	95
Figure E.21 – Three examples of design of non-isolated LPS air-termination according to the mesh method air-termination design	98
Figure E.22 – Four examples of details of an LPS on a structure with sloped tiled roofs	100
Figure E.23 – Air-termination and visually concealed conductors for buildings less than 20 m high, with sloping roofs	101
Figure E.24 – Construction of an LPS using natural components on the roof of the structure	103
Figure E.25 – Positioning of the external LPS on a structure made of isolating material e.g. wood or bricks with a height up to 60 m with flat roof and with roof fixtures	104
Figure E.26 – Construction of air-termination network on a roof with conductive covering where puncturing of the covering is not acceptable	105
Figure E.27 – Construction of external LPS on a structure of steel-reinforced concrete using the reinforcement of the outer walls as natural components	106
Figure E.28 – Example of an air-termination stud used on car park roofs	107
Figure E.29 – Air-termination rod used for protection of a metallic roof fixture with electric power installations which are not bonded to the air-termination system	108
Figure E.30 – Method of achieving electrical continuity on metallic parapet capping	109
Figure E.31 – Metallic roof fixture protected against direct lightning interception, connected to air-termination system	112

- 4 -

Figure E.32 – Examplesof lightning protection of a house with a TV antenna	. 115
Figure E.33 – Installation of lightning protection of metallic equipment on a roof against a direct lightning flash	. 116
Figure E.34 – Connection of natural air-termination rod to air-termination conductor	. 118
Figure E.35 – Construction of the bridging between the segments of the metallic facade plates	. 119
Figure E.36 – Installation of external LPS on a structure of insulating material with different roof levels	. 122
Figure E.37 – Five examples of geometry of LPS conductors	. 123
Figure E.38 – Construction of an LPS using only two down-conductors and foundation earth electrodes	. 124
Figure E.39 – Four examples of connection of earth-termination to the LPS of structures using natural down-conductors (girders) and detail of a test joint	. 128
Figure E.40 – Construction of foundation earth ring for structures of different foundation design	. 132
Figure E.41 – Two examples of vertical electrodes in type A earthing arrangement	. 134
Figure E.42 – Meshed earth-termination system of a plant	. 137
Figure E.43 – Example of an equipotential bonding arrangement	. 144
Figure E.44 – Example of bonding arrangement in a structure with multiple point entries of external conductive parts using a ring electrode for interconnection of bonding bars.	. 145
Figure E.45 – Example of bonding in the case of multiple point entries of external conductive parts and an electric power or communication line using an internal ring conductor for interconnection of the bonding bars	. 146
Figure E.46 – Example of bonding arrangement in a structure with multiple point entries of external conductive parts entering the structure above ground level	. 147
Figure E.47 – Directions for calculations of the separation distance, <i>s</i> , for a worst case lightning interception point at a distance <i>l</i> from the reference point according to 6.3	. 149
Table 1 – Relation between lightning protection levels (LPL) and class of LPS (see IEC 62305-1)	16
Table 2 – Maximum values of rolling sphere radius, mesh size and protection angle corresponding to the class of LPS	19
Table 3 – Minimum thickness of metal sheets or metal pipes in air-termination systems	21
Table 4 – Typical preferred values of the distance between down-conductors according to the class of LPS	22
Table 5 – LPS materials and conditions of use	28
Table 6 – Material, configuration and minimum cross-sectional area of air-termination conductors, air-termination rods, earth lead-in rods and down-conductors.	30
Table 7 – Material, configuration and minimum dimensions of earth electrodes	31
Table 8 – Minimum dimensions of conductors connecting different bonding bars or connecting bonding bars to the earth-termination system	33
Table 9 – Minimum dimensions of conductors connecting internal metal installations to the bonding bar	33
Table 10 – Isolation of external LPS – Values of coefficient k_i	35
Table 11 – Isolation of external LPS – Values of coefficient $k_{\rm m}$	35
Table 12 – Isolation of external LPS – Approximated values of coefficient k_{c}	36
Table B.1 – Cable length to be considered according to the condition of the screen	45
Table E.1 – Suggested fixing centres.	99

Table E.2 – Maximum period between inspections of an LPS 1	151
--	-----

- 6 -

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PROTECTION AGAINST LIGHTNING –

Part 3: Physical damage to structures and life hazard

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62305-3 has been prepared by IEC technical committee 81: Lightning protection.

This second edition cancels and replaces the first edition, published in 2006, and constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- 1) Minimum thicknesses of metal sheets or metal pipes given in Table 3 for air-termination systems are assumed as not able to prevent hot-spot problems.
- 2) Steel with electro-deposited copper is introduced as material suitable for LPS.
- 3) Some cross-sectional areas of LPS conductors were slightly modified.
- 4) For bonding purposes, isolating spark gaps are used for metal installations and SPD for internal systems.

- 5) Two methods simplified and detailed are provided for evaluation of separation distance.
- 6) Protection measures against injuries of living beings due to electric shock are considered also inside the structure.
- 7) Improved information for LPS in the case of structures with a risk of explosion are given in Annex D (normative).

The text of this standard is based on the following documents:

FDIS	Report on voting
81/372/FDIS	81/382/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted, as closely as possible, in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts in the IEC 62305 series, under the general title *Protection against lightning*, can be found on the IEC website.