საქართველოს სტანდარტი

ტრანსპორტირებადი ვენტილირებადი ოთახები ფუნქციონირების შიდა წყაროთი ან მის გარეშე

> საქართველოს სტანდარტებისა და მეტროლოგიის ეროვნული სააგენტო თბილისი

სსტენ 50381:2004/2015

საინფორმაციო მონაცემები

- 1 დამტკიცებულია და შემოღებულია სამოქმედოდ საქართველოს სტანდარტებისა და მეტროლოგიის ეროვნული სააგენტოს 2015 წლის 27 მარტის № 21 და 2015 წლის 10 თებერვლის № 9 განკარგულებებით
- **2 მიღებულია გარეკანის თარგმნის მეთოდით** სტანდარტიზაციის ევროპული კომიტეტის სტანდარტი ენ 50381:2004 ,, ტრანსპორტირებადი ვენტილირებადი ოთახები ფუნქციონირების შიდა წყაროთი ან მის გარეშე"

3 პირველად

4 რეგისტრირებულია საქართველოს სტანდარტებისა და მეტროლოგიის ეროვნული სააგენტოს რეესტრში: 2015 წლის 27 მარტი №268-1.3-7025

EUROPEAN STANDARD NORME EUROPÉENNE

EUROPÄISCHE NORM

EN 50381

August 2004

ICS 29.260.20

Incorporates Corrigendum December 2005

English version

Transportable ventilated rooms with or without an internal source of release

Caissons ventilés transportables avec ou sans source de dégagement interne

Transportable ventilierte Räume mit oder ohne innere Freisetzungsstelle

This European Standard was approved by CENELEC on 2004-03-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

Foreword

This European Standard was prepared by WG 31-73, of SC 31-7, Pressurization and other techniques, of the Technical Committee CENELEC TC 31, Electrical apparatus for explosive atmospheres.

The text of the draft was submitted to the Unique Acceptance Procedure and was approved by CENELEC as EN 50381 on 2004-03-01.

The following dates were fixed:

 latest date by which the EN has to be implemented at national level by publication of an identical national standard or by endorsement

(dop) 2005-03-01

 latest date by which the national standards conflicting with the EN have to be withdrawn

(dow) 2007-03-01

This standard covers the essential requirements for pressurized rooms without an internal source of release and the additional requirements when an internal source of release is present.

This European Standard was prepared under mandate BC/CEN/CLC/08-92 given to CENELEC by the European Commission and the European Free Trade Association and covers essential requirements of the EC Directive 94/9/EC. See Annex ZZ.

This European Standard is to be read in conjunction with EN 50014, Electrical apparatus for potentially explosive atmospheres – General requirements, or where appropriate, with EN 50021, Electrical apparatus for potentially explosive atmospheres – Type of protection "n". This European Standard should not be considered in conjunction with any editions of these standards and their amendments published before 1997.

The contents of the corrigendum of December 2005 have been included in this copy.

Contents

			Page		
1	Scope				
2	Normative references				
3	Definitions				
4	Cons	truction requirements for TVR's and ducting	10		
	4.1	General			
	4.2	Degree of ingress protection			
	4.3	Design and construction			
	4.4	Mechanical strength			
	4.5	Penetrations			
	4.6	Floor drains	11		
	4.7	Floors	11		
	4.8	Doors	11		
	4.9	Inspection window(s)	11		
	4.10	Apertures	12		
	4.11	Enclosures	12		
5	Requ	irements for TVR's, equipment group I, type of protection vM2	12		
6	Venti	lation requirements for TVR's, equipment group II	13		
7	Addit	ional ventilation requirements for TVR'S with an internal source of release	13		
8	Temr	perature limits	14		
9		num safety provisions and devices			
10		ional safety provisions and devices for TVR's meeting the requirements of type			
10		otection v2 and vM2			
11	Addit	ional requirements for TVR's with an internal source of release	16		
	11.1	Assessment of containment systems	16		
		Release conditions			
		11.2.1 No release	16		
		11.2.2 Release of a flammable liquid	17		
	11.3	Design requirements for the containment system	17		
		11.3.1 Infallible parts of the containment system	17		
		11.3.2 Containment system with limited release			
	11.4	Ignition capable apparatus in the case of type of protection v2	18		
		Location of apparatus in the case of type of protection v3			
	11.6	Internal hot surfaces			
		11.6.1 Loss of minimum pressure differential, type of protection v2	18		
		11.6.2 Loss of ventilation flow, type of protection v2			
		11.6.3 Loss of ventilation flow, type of protection v3			
		Potential source of internal release			
12		irements for gas detectors			
13	Supp	ly of protective gas	20		
	13.1	Ventilation	20		
	13.2	Leakage Compensation of a Breathable Atmosphere (LCBA)	20		
	13.3	Density limits	21		

14	Туре	verification and tests	.21	
	14.1	Sequence of tests	.21	
	14.2	Thermal tests	.21	
	14.3	Overpressure test	.21	
	14.4	Purging test	.22	
	14.5	Verification of minimum pressure differential	.22	
	14.6	Ventilation flow rate tests for TVR's with an internal source of release	.23	
	14.7	Overpressure test for containment systems with limited release	.23	
	14.8	Verification of sequence of operation of the safety devices	.23	
	14.9	Additional tests	.23	
15	Routine tests			
	15.1	Test conditions	.23	
	15.2	Verification of minimum pressure differential	.23	
	15.3	Ventilation flow rate tests for TVR's with an internal source of release	.24	
	15.4	Overpressure test for containment systems with limited release	.24	
	15.5	Verification of sequence of operation of the safety devices	.24	
	15.6	Additional tests	.24	
16	Mark	ing	.24	
	16.1	TVR's all cases	.24	
	16.2	TVR's with a containment system	.25	
	16.3	Safety related control systems	.25	
	16.4	Additional marking	.25	
17	Instru	ıctions	.25	
Anne	ex A	(normative) Method of protection of electrical apparatus containing a potential		
		f a flammable gas or vapour	.26	
	A.1	Introduction	.26	
	A.2	Definitions	.26	
	A.3	Requirements	.26	
		(normative) Method of protection of electrical apparatus containing a potential f a flammable liquid	.29	
1	B.1	Introduction	.29	
I	B.2	Definitions	.29	
1	B.3	Requirements	.29	
	B.4	Flammable non-flashing liquids	.30	
1	B.5	Spark and particle barriers	.31	
	B.6	Flashing liquids	.32	
		(informative) Determination of peak rise in enclosure pressure, resulting from an elease of a flashing liquid	.33	
	C.1	Introduction	.33	
(C.2	Definitions		
		(informative) Method of protection of electrical apparatus containing a potential f a flammable gas or vapour		
		(informative) Mathematical model of dilution of a source of release		
		phy		
		(informative) Coverage of Essential Requirements of EC Directives		
		TORROGOVEL SOVERAGE OF ESSERIAL RECONCENEOUS OF EU-DITECTIVES		

Introduction

This is a new European Standard for transportable pressurized rooms with and without an internal source of release but is confined to those rooms which are transportable and should not apply to rooms constructed on site and not intended for resale.

Pressurized rooms are locations intended for human occupation under normal operational circumstances. In such circumstances it is important to distinguish between pressurization, which may use air or inert gas and be applied to apparatus not required to support life, from ventilation. Ventilation in the context of this standard, taken together with other safety measures, ensures a safe (and breathable) atmosphere within the pressurized room.

This text is based upon the scope of EN 61285, IEC/TR 61831, IEC 60079-13 and IEC 60079-16 and the essential safety requirements of Directive 94/9/EC.