

## საქართველოს სტანდარტი

შესაძლებლობების გამოვლენა-ნაწილი 2: მეტროლოგია ხაზოვანი  
კალიბრაციის შემთხვევებში

საქართველოს სტანდარტებისა და მეტროლოგიის  
ეროვნული სააგენტო  
თბილისი

საინფორმაციო მონაცემები

1 დამტკიცებულია და შემოღებულია სამოქმედოდ საქართველოს სტანდარტებისა და მეტროლოგიის ეროვნული სააგენტოს 2015 წლის 17 მარტის № 19 და 2015 წლის 10 თებერვლის № 9 განკარგულებებით

2 მიღებულია გარეკანის თარგმნის მეთოდით სტანდარტიზაციის საერთაშორისო ორგანიზაციის სტანდარტი ისო 11843-2:2000 „ შესაძლებლობების გამოვლენა-ნაწილი 2: მეტროლოგია ხაზოვანი კალიბრაციის შემთხვევებში“

3 პირველად

4 რეგისტრირებულია საქართველოს სტანდარტებისა და მეტროლოგიის ეროვნული სააგენტოს რეესტრში: 2015 წლის 17 მარტი №268-1.3-6798

აკრძალულია ამ სტანდარტის გადაცემა მესამე პირებისათვის ან/და მისი სხვა ფორმით გავრცელება

საინფორმაციო ნაწილი. სრული ტექსტის სანახავად შეიძინეთ სტანდარტი.

# INTERNATIONAL STANDARD

# ISO 11843-2

First edition  
2000-05-01

---

---

## Capability of detection —

Part 2:

## Methodology in the linear calibration case

*Capacité de détection —*

*Partie 2: Méthodologie de l'étalonnage linéaire*



Reference number  
ISO 11843-2:2000(E)

© ISO 2000

საინფორმაციო ნაწილი. სრული ტექსტის სანახავად შეიძინეთ სტანდარტი.

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

საინფორმაციო ნაწილი. სრული ტექსტის სანახავად შეიძინეთ სტანდარტი.

© ISO 2000

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 734 10 79  
E-mail [copyright@iso.ch](mailto:copyright@iso.ch)  
Web [www.iso.ch](http://www.iso.ch)

Printed in Switzerland

## Contents

|   |           |
|---|-----------|
| Foreword.....   | iv        |
| Introduction.....   | v         |
| <b>1</b> <b>Scope</b> .....   | <b>1</b>  |
| <b>2</b> <b>Normative references</b> .....  | <b>1</b>  |
| <b>3</b> <b>Terms and definitions</b> .....   | <b>2</b>  |
| <b>4</b> <b>Experimental design</b> .....   | <b>2</b>  |
| <b>4.1</b> <b>General</b> .....   | <b>2</b>  |
| <b>4.2</b> <b>Choice of reference states</b> .....  | <b>2</b>  |
| <b>4.3</b> <b>Choice of the number of reference states, <math>I</math>, and the (numbers of) replications of procedure, <math>J</math>,<br/>          <math>K</math> and <math>L</math></b> ..... | <b>3</b>  |
| <b>5</b> <b>The critical values <math>y_C</math> and <math>x_C</math> and the minimum detectable value <math>x_d</math> of a measurement series</b> .....   | <b>3</b>  |
| <b>5.1</b> <b>Basic assumptions</b> .....   | <b>3</b>  |
| <b>5.2</b> <b>Case 1 — Constant standard deviation</b> .....  | <b>4</b>  |
| <b>5.3</b> <b>Case 2 — Standard deviation linearly dependent on the net state variable</b> .....  | <b>6</b>  |
| <b>6</b> <b>Minimum detectable value of the measurement method</b> .....  | <b>9</b>  |
| <b>7</b> <b>Reporting and use of results</b> .....  | <b>10</b> |
| <b>7.1</b> <b>Critical values</b> .....   | <b>10</b> |
| <b>7.2</b> <b>Minimum detectable values</b> .....   | <b>10</b> |
| <b>Annex A</b> (normative) <b>Symbols and abbreviations</b> .....   | <b>11</b> |
| <b>Annex B</b> (informative) <b>Derivation of formulae</b> .....  | <b>14</b> |
| <b>Annex C</b> (informative) <b>Examples</b> .....  | <b>20</b> |
| <b>Bibliography</b> .....   | <b>24</b> |

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this part of ISO 11843 may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 11843-2 was prepared by Technical Committee ISO/TC 69, *Applications of statistical methods*, Subcommittee SC 6, *Measurement methods and results*.

ISO 11843 consists of the following parts, under the general title *Capability of detection*:

- *Part 1: Terms and definitions*
- *Part 2: Methodology in the linear calibration case*

Annex A forms a normative part of this part of ISO 11843. Annexes B and C are for information only.

საინფორმაციო ნაწილი. სრული ტექსტის სანახავად შეიძინეთ სტანდარტი.

## Introduction

An ideal requirement for the capability of detection with respect to a selected state variable would be that the actual state of every observed system can be classified with certainty as either equal to or different from its basic state. However, due to systematic and random distortions, this ideal requirement cannot be satisfied because:

- in reality all reference states, including the basic state, are never known in terms of the state variable. Hence, all states can only be correctly characterized in terms of differences from basic state, i.e. in terms of the net state variable.

In practice, reference states are very often assumed to be known with respect to the state variable. In other words, the value of the state variable for the basic state is set to zero; for instance in analytical chemistry, the unknown concentration or the amount of analyte in the blank material usually is assumed to be zero and values of the net concentration or amount are reported in terms of supposed concentrations or amounts. In chemical trace analysis especially, it is only possible to estimate concentration or amount differences with respect to available blank material. In order to prevent erroneous decisions, it is generally recommended to report differences from the basic state only, i.e. data in terms of the net state variable;

**NOTE** In the ISO Guide 30 and in ISO 11095 no distinction is made between the state variable and the net state variable. As a consequence, in these two documents reference states are, without justification, assumed to be known with respect to the state variable.

- the calibration and the processes of sampling and preparation add random variation to the measurement results.

In this part of ISO 11843, the following two requirements were chosen:

- the probability is  $\alpha$  of detecting (erroneously) that a system is not in the basic state when it is in the basic state;
- the probability is  $\beta$  of (erroneously) not detecting that a system, for which the value of the net state variable is equal to the minimum detectable value ( $x_d$ ), is not in the basic state.

საინფორმაციო ნაწილი. სრული ტექსტის სანახავად შეიძინეთ სტანდარტი.